SILENCE: The quieter option.


No blower no air! In industrial processes one blower can often supply several air heaters in parallel. Our durable and maintenance-free blowers are a result of uncompromising quality standards and decades of experience. SILENCE, Leister's mid-range blower, is very quiet during operation at 61 dB(A). Developed to withstand operating conditions with air intake temperatures of 100° C to 200° C. Delivers optimum & effortless performance in ambient temperatures up to 75° C.

Medium pressure blower


SILENCE



Technical data SILENCE Design: radial blower	■		
Frequency	Hz	50	60
Air flow (20 °C)	I/min	4700	6000
Static pressure	kPa	1.0	1.4
Max. ambient temperature	°C	75	75
Max. air inlet temperature	°C	200	200
Noise emission level	dB(A)	61	61
Environmental protection (IEC 60529)		IP 54	IP 54
Outside diameter air inlet	mm	Ø 80	Ø 80
Outside diameter air outlet	mm	Ø 60	Ø 60
Weight	kg	9.0	9.0
Conformity mark		C € (ErP n/a)	C € (ErP n/a)
Protection class I		((<u></u>
Can be controlled with FC (page	e 57), 20 – 80	Hz	



Voltage	V ~ 50 Hz V ~ 60 Hz	1 x 230	3 x 230 / 400 3 x 440 – 480	
Power consumption	W	250	250	
Without cable	Order no.		103.507	
3 m cable / Euro plug	Order no.	103.510		
Additional versions available on request				



Accessories > 58



Accessories SILENCE (Ø 60 mm)

	107.288	PVC air hose Ø 60 mm
	107.287	Hose clip for Ø 60 mm air hose
	107.240	Closing cap \varnothing 60 mm attachable to hose connection adaptor 107.238 and 107.278
	107.294	Stainless steel filter, push-fit on air intake
Y Reco	110.887	Motor capacitor 230 V
60	107.291	Hose connection adaptor with 1 air outlet for Ø 38 mm hose, push-fit on air outlet
60 60	107.278	Hose connection adaptor, push-fit on air outlet
38 60	107.292	Hose connection adaptor with 2 air outlets for Ø 38 mm hose, push-fit on air outlet
38	107.293	Hose connection adaptor, push-fit on adaptor 107.292
60 62	107.295	Manually-operated air flow adjuster Size 214 x 88 x 133 mm
62	107.296	Air flow off/on switch The air flow is interrupted on command (pneumatic 500 kPa) to the heaters. Size 214 x 88 x 133 mm